


Wall-mounted air conditioner

Roni R26X ^[R16]



- SCOP 4,0
- Wi-Fi
- 20°C
- Gold fins
- Zz
- 4D
- 5 year WARRANTY
- PZH CERTIFICATE

1:1
SINGLE

1:X
MULTI

Unit features

 Digital DC Inverter SKY®	 Automatic cleaning iAIR	 Automatic purification iClean ⁽¹⁾	 3-in-1 (Ca + Si.Ion + Vit.C) iAIR filter ^(*)	 3w1 (Photo. + Act. Carb. + Nano) iAIR filter ^(**)	 Electrostatic HD iAIR filter	 Super Silent eMOTO mode	 Automatic 4D louvres
 Turbo eMOTO mode	 Air supply eMOTO control system	 ECO eMOTO mode	 Wide-angle eMOTO air supply	 SMART wi-fi	 SMART panel display ON/OFF	 SMART Follow mode ⁽¹⁾	 Wireless remote control
 SMART heating to 8°C ⁽¹⁾	 Auto restart memory	 Anti-corrosive gold fins	 Timer	 Cooling at low outdoor temp. down to -15°C	 Heating at low outdoor temp. down to -20°C	 Double-sided condensate drainage	 Self-diagnostics
 Sleep mode							

1. Function not available in the Multi Split system.

* 3-in-1 iAIR filter: Catechin + Silver Ion + Vitamin C

** 3-in-1 iAIR filter: Photocatalytic + Activated carbon + Cold Nano

Technical specification

Model				Roni 2,6 kW
Capacity	Cooling	Nom. (Min. - Max.)	W	2600 (940-3300)
Rated input		Nom. (Min. - Max.)	W	825 (240-1380)
Operating current		Nom. (Min. - Max.)	A	3,6 (1,0-6,0)
Capacity	Heating	Nom. (Min. - Max.)	W	2610 (940-3360)
Rated input		Nom. (Min. - Max.)	W	767 (240-1552)
Operating current		Nom. (Min. - Max.)	A	3,3 (1,0-6,7)
Reversible heat pump type				air-to-air
Design load in cooling mode			kW	2,6
SEER			W/W	6,1
Energy efficiency class, cooling				A++
Annual electric energy consumption, cooling			kWh/a	149
Design load in heating mode (T _{biv} -7°C)			kW	2,0
SCOP			W/W	4,0
Energy efficiency class, heating				A+
Annual electric energy consumption, heating			kWh/a	700
Dehumidification			l/h	1,0
Maximum energy consumption			W	1552
Maximum operating current			A	6,7
Indoor unit				R26Xi R16
EAN product code				5905567601460
Fan speed	T / H / M / L / S	rpm	1400 / 1300 / 1100 / 1000 / 900	
Air flow	T / H / M / L / S	m³/h	490 / 390 / 330 / 300 / 270	
Sound pressure level	T / H / M / L / S	dB(A)	40 / 37 / 33 / 25 / 22	
Sound power level		dB(A)	50	
Rated input		W	30	
Operating current		A	0,1	
Net dimensions	W × D × H	mm	698 × 205 × 255	
Gross dimensions	W × D × H	mm	765 × 260 × 335	
Net weight / Gross weight		kg	6,5 / 8,5	
Condensate drain		mm	16	
Outdoor unit				R26Xo R16
EAN product code				5905567601507
Fan speed	T / H / M / L / S	rpm	930 / 930 / 830 / 730 / 630	
Maximum air flow		m³/h	1700	
Sound pressure level		dB(A)	50	
Sound power level		dB(A)	60	
Net dimensions	W × D × H	mm	740 × 253 × 459	
Gross dimensions	W × D × H	mm	765 × 310 × 481	
Bracket spacing	W × D	(mm)	362 × 256	
Net weight / Gross weight		kg	22 / 24	
Refrigerant	Type		R32	
	GWP		675	
	≤ 5m	kg	0,45	
		TCO ₂ eq	0,30	
Charged (> 5m)	g/mb	12		
Pipe connections	Liquid/Gas	mm (inches)	Φ6,35 / Φ9,52 (1/4" / 3/8")	
Maximum installation length		m	25	
Maximum height difference		m	10	
Compressor type				Rotary DC
Type of outdoor unit power supply			V-Hz, Ø	220-240-50, 1f
Electrical protection			A	C16
Power cables: outdoor unit			pcs × mm²	3 × 1,5
Control and power cables: indoor unit - outdoor unit			pcs × mm²	4 × 1
Control and power cables: hiro unit - indoor unit			pcs × mm²	4 × 1
Indoor operating range (Cooling / Heating)			°C	16~32 / 0~30
Outdoor operating range (Cooling / Heating)			°C	-15~53 / -20~30
Compatible systems				
1:1 SINGLE				•
1:2 DUAL				
1:X MULTI S-Line				
1:X MULTI N-Line				•

T - Turbo; H - High; M - Middle; L - Low; S - Silent