

Wall-mounted air conditioner

Versu Cloth Caramel VCC50X ^[R15]



- SCOP 4,1
- WiFi
- 22°C
- 4-way air flow
- Heating coil
- Heating coil
- 5 year WARRANTY
- PZH CERTIFICATE

- DEDICATED TO HEATING
- 1:1 SINGLE
- 1:X MULTI

Unit features

SKY inverter Digital DC Inverter SKY [®]	Textile changeable front panel	Automatic purification iClean ⁽¹⁾	Super Ionizer iAIR	3-in-1 (Si,Ion + Photocat. + Nano) iAIR filter ⁽¹⁾	Antibacterial HEPA iAIR filter	Electrostatic HD iAIR filter	Super Silent eMOTO mode ⁽¹⁾
Automatic 4D louvres	Rotating louvre 180°	Turbo eMOTO mode ⁽¹⁾	Upwards cascade air supply	Downwards cascade air supply	Air supply eMOTO control system	Eco eMOTO mode ⁽¹⁾	Wide-angle eMOTO air supply
Humidity sensor ⁽¹⁾⁽²⁾	SMART wi-fi	Wired controller SMART port ⁽²⁾	SMART panel display ON/OFF	SMART Follow mode	Wireless remote control	Wired controller ⁽²⁾	SMART heating to 8°C ⁽¹⁾
Louvre setting memory	1W standby mode ⁽¹⁾	Auto restart memory	Anti-corrosive gold fins	Drip tray heater	Compressor crankcase heater	Silence mode	Timer
Cooling at low outdoor temp. down to -15°C	Heating at low outdoor temp. down to -22°C ⁽¹⁾	Double-sided condensate drainage	Self-diagnostics	Sleep mode	BMS Modbus ⁽²⁾	BMS Bacnet ⁽²⁾	

1. Feature not available in Multi Split system. 2. Feature is only optional. 3. Feature can be accessed via mobile app.

* Silver Ion + Photocatalytic + Cold Nano

Technical specification

Model				Versu Cloth Caramel 5,3 kW	
Capacity	Cooling	Nom. (Min. - Max.)	W	5275 (1817-6008)	
Rated input		Nom. (Min. - Max.)	W	1600 (140-2300)	
Operating current		Nom. (Min. - Max.)	A	7,0 (0,6-10,0)	
Capacity	Heating	Nom. (Min. - Max.)	W	5568 (1260-6154)	
Rated input		Nom. (Min. - Max.)	W	1680 (220-2350)	
Operating current		Nom. (Min. - Max.)	A	7,3 (1,0-10,2)	
Reversible heat pump type				air-to-air	
Design load in cooling mode			kW	5,3	
SEER			W/W	6,3	
Energy efficiency class, cooling				A++	
Annual electric energy consumption, cooling			kWh/a	294	
Design load in heating mode (Tbiv -7°C)			kW	4,1	
SCOP			W/W	4,1	
Energy efficiency class, heating				A+	
Annual electric energy consumption, heating			kWh/a	1430	
Dehumidification			l/h	1,8	
Maximum energy consumption			W	2500	
Maximum operating current			A	10,9	
Indoor unit				VCC50Xi R15	
EAN product code				5905567601057	
Fan speed	T / H / M / L / ML / S	rpm	1150 / 970 / 880 / 800 / 760 / 670		
Air flow	T / H / M / L / ML / S	m³/h	750 / 590 / 490 / 410 / 330 / 280		
Sound pressure level	T / H / M / L / ML / S	dB(A)	41 / 36 / 30 / 28 / 24 / 19		
Sound power level		dB(A)	54		
Rated input		W	34		
Operating current		A	0,1		
Net dimensions	W × D × H	mm	920 × 211 × 321		
Gross dimensions	W × D × H	mm	1005 × 295 × 385		
Net weight / Gross weight		kg	11,5 / 14,4		
Condensate drain		mm	16		
Outdoor unit				VO50Xo R15	
EAN product code				5905567606687	
Fan speed	H / M / L	rpm	760 / 650 / 490		
Maximum air flow		m³/h	2100		
Sound pressure level		dB(A)	54		
Sound power level		dB(A)	63		
Net dimensions	W × D × H	mm	805 × 330 × 554		
Gross dimensions	W × D × H	mm	915 × 370 × 615		
Bracket spacing	W × D	(mm)	511 × 317		
Net weight / Gross weight		kg	33,5 / 36,1		
Refrigerant	Type		R32		
	GWP		675		
	≤ 5m	kg	1,1		
		TCO ₂ eq	0,74		
Charged > 5m	g/mb	12			
Pipe connections	Liquid/Gas	mm (inches)	Φ6,35 / Φ12,7 (1/4" / 1/2")		
Maximum installation length		m	30		
Maximum height difference		m	20		
Compressor type				Rotary DC	
Type of outdoor unit power supply			V-Hz, Ø	220-240-50, 1f	
Electrical protection			A	C16	
Power cables: outdoor unit			pcs × mm²	3 × 2,5	
Control and power cables: indoor unit - outdoor unit			pcs × mm²	5 × 2,5	
Control and power cables: hiro unit - indoor unit			pcs × mm²	4 × 1,5	
Indoor operating range (cooling / heating)			°C	16~32 / 0~30	
Outdoor operating range (cooling / heating)			°C	-15~50 / -22~30	
Compatible systems					
1:1 SINGLE				•	
1:2 DUAL					
1:X MULTI S-Line				•	
1:X MULTI N-Line					