


Aquami Monoblock heat pump

AQM60X1 ^[R14]



Device features

 Environmentally friendly refrigerant R32	 Efficient heating	 Energy efficiency class at 35°C A+++	 Energy efficiency class at 55°C A++	 Maximum COP 4,95	 Operating range down to -25°C	 Supply water temperature of 65°C	 Integrated USB port for updates
 Energy meter	 Smart Grid functionality	 Twin rotary compressor	 Integrated electric heater	 Outdoor unit drip tray heater	 Compressor crankcase heater	 Easy installation and maintenance	 Silent mode
 Wired controller Wi-Fi module	 Configurable daily schedules	 Configurable weekly schedules	 Vacation mode	 Menu in English	 Multilanguage menu	 Integrated temperature sensor	 Weather operating modes (climate curve)
 2 heating control zones	 Dedicated application	 Disinfection	 DHW circulation pump operation schedules	 Maximum leaving water temperature of 60°C (in DHW mode)	 Prepared to create a cascade system		

Specification outdoor unit

Model			AQM60X1 R14	
EAN Code			5905567602184	
Power supply		V-Hz, Ø	220-240-50, 1f	
Heating (A7W35)	Capacity	kW	6,35	
	Rated input	kW	1,28	
	COP		4,95	
Heating (A7W45)	Capacity	kW	6,30	
	Rated input	kW	1,70	
	COP		3,70	
Heating (A7W55)	Capacity	kW	6,00	
	Rated input	kW	2,03	
	COP		2,95	
Cooling (A35/W18)	Capacity	kW	6,50	
	Rated input	kW	1,35	
	EER		4,80	
Cooling (A35/W7)	Capacity	kW	7,00	
	Rated input	kW	2,33	
	EER		3,00	
Seasonal energy efficiency LWT at 35°C	SCOP ⁽¹⁾		4,95	
	Rated heat output	kW	6,8	
	Seasonal energy efficiency ratio (η _S)	%	195	
	Annual energy consumption	kWh	2845	
	Seasonal space heating energy efficiency class ⁽¹⁾		A+++	
Seasonal energy efficiency LWT at 55°C	SCOP ⁽¹⁾		3,52	
	Rated heat output	kW	5,70	
	Seasonal energy efficiency ratio (η _S)	%	137,9	
	Annual energy consumption	kWh	3343	
	Seasonal space heating energy efficiency class ⁽¹⁾		A++	
SEER	LWT at 7°C		5,34	
	LWT at 18°C		8,21	
Minimum rated current of the overcurrent circuit breaker with breaker type		A	B32	
Compressor		Type	Twin rotary inverter compressor DC	
Fan		Type	Brushless DC motor / BLDC	
		Quantity	1	
Refrigerant		Type / GWP	R32 / 675	
		Quantity	1,4	
		TCO _{eq}	0,95	
Minimal wire pcs and dimension of cords*		pcs × mm ²	3 × 6	
Bracket spacing (W1×W2×D)		mm	638 × 379 × 401	
Sound pressure level		dB(A)	47,5	
Sound power level		dB(A)	58	
Net dimensions (W×D×H)		mm	1295×429×718	
Gross dimensions (W×D×H)		mm	1375×475×885	
Net weight / Gross weight		kg	91/112	
Operating outdoor temperature	Cooling	°C	-5-43	
	Heating	°C	-25-35	
	DHW	°C	-25-43	
Operation modes			Heating and cooling	
Leaving water temperature	Space cooling	°C	5-25	
	Space heating	°C	25-65	
	DHW (tank)	°C	30-60	
Electric heater	Power supply	V-Hz, Ø	220-240-50, 1f	
	Number of heating stages / Power	pcs / kW	1 / 3	
	Maximum operating current	A	13,5	
Water circuit	Water connections		mm (inch)	33mm (G1" BSP) external
	Pressure relief valve		MPa	0,3
	Condensate drain		mm	16
	Expansion tank	Total volume / Actual volume	l	8 / 4,8
		Maximum pressure / Initial pressure	MPa	0,3 / 0,1
	Heat exchanger	Type		PHE / plate heat exchanger
		Minimum flow	l/min	6
	Water pump head		m	9
	Water pump type			DC
Total water volume		l	3,2	

(1) Seasonal energy efficiency class measured under average climate conditions.

Notes: DHW - Domestic hot water, LWT - Leaving water temperature

The sound pressure level is measured 1m in front of the unit and (1+H)/2m (where H is the height of the unit) above the floor in semi-anechoic room. During on-site operation sound pressure levels can be higher as a result of ambient noise. Sound pressure level and sound power level reflect the maximum value tested under three conditions specified respectively in notes A7W35, ΔT=5; A7W45, ΔT=5; A7W55 ΔT=8; relative humidity 85%. The figures specified above refer to the following standards: EN14511; EN14825; EN50564; EN12102; (EU) Np. 811/2013; (EU) No. 813/2013; Journal of Laws 2014 / C 207/02: 2014.

The residual current circuit breaker used to protect the electrical circuit of the appliance shall be selected in view of the electrical regulations in force, assuming that the rated residual current is not greater than I_{Δn}: 30mA

*The above values apply to supply cables with a maximum length of 20mb. If this value is exceeded, an electrical designer should be consulted.