

Wall-mounted air conditioner

Elis Silver ES70X ^[R15]



- SCOP 4,0
- Wi-Fi
- 20°C
- iAIR
- Zz
- 4D
- 5 year WARRANTY
- PZH CERTIFICATE

1:1
SINGLE

Unit features

 Digital DC Inverter SKY®	 Automatic cleaning iAIR	 Automatic purification iClean	 3-in-1 (Ca + Si.Ion + Vit.C) iAIR filter (*)	 3-in-1 (Photo. + Act. Carb. + Nano) iAIR filter (**)	 Electrostatic HD iAIR filter	 Super Silent eMOTO mode	 Automatic 4D louvres
 Turbo eMOTO mode	 Air supply eMOTO control system	 ECO eMOTO mode	 Wide-angle eMOTO air supply	 SMART wi-fi	 SMART panel display ON/OFF	 SMART Follow mode	 Wireless remote control
 SMART heating to 8°C	 Auto restart memory	 Anti-corrosive gold fins	 Timer	 Cooling at low outdoor temp. down to -15°C	 Heating at low outdoor temp. down to -20°C	 Double-sided condensate drainage	 Self-diagnostics
 Sleep mode							

* 3-in-1 iAIR filter: Catechin + Silver Ion + Vitamin C
** 3-in-1 iAIR filter: Photocatalytic + Activated carbon + Cold Nano

Technical specification

Model				Elis Silver 6,8 kW	
Capacity	Cooling	Nom. (Min. - Max.)	W	6810 (1830-7800)	
Rated input		Nom. (Min. - Max.)	W	2257 (410-2824)	
Operating current		Nom. (Min. - Max.)	A	9,8 (1,8-12,3)	
Capacity	Heating	Nom. (Min. - Max.)	W	6870 (1850-7900)	
Rated input		Nom. (Min. - Max.)	W	2063 (420-3005)	
Operating current		Nom. (Min. - Max.)	A	9,0 (1,8- 13,0)	
Reversible heat pump type				air-to-air	
Design load in cooling mode			kW	6,8	
SEER			W/W	6,1	
Energy efficiency class, cooling				A++	
Annual electric energy consumption, cooling			kWh/a	390	
Design load in heating mode (T _{biv} -7°C)			kW	4,5	
SCOP			W/W	4,0	
Energy efficiency class, heating				A+	
Annual electric energy consumption, heating			kWh/a	1680	
Dehumidification			l/h	1,8	
Maximum energy consumption			W	3005	
Maximum operating current			A	13,1	
Indoor unit				ES70Xi R15	
EAN product code				5905567601378	
Fan speed	T / H / M / L / S		rpm	1250 / 1200 / 1050 / 950 / 800	
Air flow	T / H / M / L / S		m³/h	980 / 920 / 800 / 690 / 540	
Sound pressure level	T / H / M / L / S		dB(A)	44 / 41 / 38 / 34 / 30	
Sound power level			dB(A)	57	
Rated input			W	50	
Operating current			A	0,2	
Net dimensions		W × D × H	mm	1010 × 220 × 315	
Gross dimensions		W × D × H	mm	1094 × 300 × 386	
Net weight / Gross weight			kg	13 / 16	
Condensate drain			mm	16	
Outdoor unit				EO70Xo R15	
EAN product code				5905567601330	
Fan speed	H / M / L		rpm	930 / 830 / 690 / 570 / 450	
Maximum air flow			m³/h	3000	
Sound pressure level			dB(A)	57	
Sound power level			dB(A)	67	
Net dimensions		W × D × H	mm	845 × 336 × 693	
Gross dimensions		W × D × H	mm	960 × 400 × 732	
Bracket spacing		W × D	(mm)	586 × 347	
Net weight / Gross weight			kg	40 / 43	
Refrigerant	Type			R32	
	GWP			675	
	≤ 5m	kg		1,14	
		TCO ₂ eq		0,77	
Charged (> 5m)		g/mb		12	
Pipe connections		Liquid/Gas	mm (inches)	Φ6,35 / Φ12,7 (1/4" / 1/2")	
Maximum installation length			m	25	
Maximum height difference			m	10	
Compressor type				Rotary DC	
Type of outdoor unit power supply			V-Hz, Ø	220-240-50, 1f	
Electrical protection			A	C25	
Power cables: outdoor unit			pcs × mm²	3 × 2,5	
Control and power cables: indoor unit - outdoor unit			pcs × mm²	4 × 1	
Control and power cables: hiro unit - indoor unit			pcs × mm²	-	
Indoor operating range (Cooling / Heating)			°C	16-32 / 0-30	
Outdoor operating range (Cooling / Heating)			°C	-15-53 / -20-30	
Compatible systems					
1:1 SINGLE				●	
1:2 DUAL					
1:X MULTI S-Line					
1:X MULTI N-Line					