

Floor/ceiling unit

Jato FC RVF-45V4IFC ^[R11]



Device features

Refrigerant R410A	Versatile RVF indoor unit	Built-in EXV valve	Automatic 4D louvres	SMART Follow mode	Electrostatic HD iAIR filter	Air supply eMOTO control system	Eco eMOTO mode
Sleep mode	Wide-angle eMOTO air supply	SMART LED temperature display	Automatic addressing	Manual addressing	Wireless remote control	Controller with IrDA receiver ⁽¹⁾	Wired controller port
Central controller output	Auto restart memory	Louvre setting memory	Synchronous operation	Dry Contact output	Freon leakage indication	Alarm output	Timer
Double-sided condensate drainage	Self-diagnostics	SMART Wi-Fi ⁽²⁾	Compatibility with BMS ⁽³⁾				

1. Wired controller available as an option only

2. Requires optional Wi-Fi

3. Requires optional BMS gateway

Technical specification

Model			RVF-45V4IFC R11
Power supply		V-Hz, Ø	220-240~50, 1f
Capacity	Cooling	kW	4,5
		BTU/h	15355
	Heating	kW	5,0
		BTU/h	17061
Rated input		W	40
Operating current		A	0,2
Fan motor		Type	DC
Air flow		m³/h	550
Sound pressure level		dB(A)	33~38
Unit dimensions (W×H×D)	Net	mm	1050 × 675 × 235
	Gross	mm	1130 × 765 × 330
Weight	Net	kg	26,5
	Gross	kg	31,0
Connections	Liquid/Gas	mm (in)	Φ6,35 / Φ12,7 (1/4" / 1/2")
	Condensate	mm	Φ25
Cables	PQE communication	pcs. × mm²	2 × 0.75-1.0 (shielded)
	Power supply	pcs. × mm²	according to the electrical system design