

## Thermos InoxAQT300IX1 [R13]



## Device features

A tank for domestic hot water storage, equipped with one coil with a large heat exchange surface to cooperate with heat pumps.

The tank body, connections and coils are made of 316L stainless steel and all is insulated with hard, dense polyurethane foam. This ensures that the tank remains durable over a long service life.

Standard equipment includes a 3kW electric heater and a pressure relief valve.

- Capacity 200 to 500 litres
- Single coil
- •12 year tank warranty
- 1 year heater and pressure relief valve warranty
- 3kW electric heater

Model EAN Code			AQT3001X1 R13 5905567602955
Colour		White	
Tank material		Stainless steel	
Housing material		Steel	
Maximum pressure	bar	6	
Insulation thickness	mm	40	
Maximum temperature	°C	85	
Height	mm	1600	
External diameter	mm	600	
Net weight	kg	74 / 84,4	
Integrated electric	Power	kW	3
heater	Power supply	V-Hz, Ø	220-240 ~50, 1f
Magnesium anode	Upper / Bottom	inches/screw	
Heat exchanger	Туре		Single coil
	Material		Stainless steel
	Maximum pressure	bar	10
	Maximum temperature	°C	95
	Heat pump tank coil surface	m <sup>2</sup>	3,2
	Power (50/10/45°C)	kW	
	Power (60/10/45°C)	kW	48,1
	Solar coil surface	m²	
	Power (80/10/45°C)	kW	
	Capacity	l/h	1180,9
Hydraulic connections	Heat pump input	thread inches	1"
	Heat pump output	thread inches	1"
	DHW output	thread inches	1"
	Cold water input	thread inches	1"
	Temppressure valve	thread inches	1/2"
	Circulation / return	thread inches	3/4"
	Heater connection	thread inches	1 3/4"
	Solar system input	thread inches	
	Solar system output	thread inches	
Warranty	Tank	years -	12
	Heater and safety valve		1
Energy efficiency class			C
Maintenance			Obligatory service after 12 months
Static heat loss W			92

## Specification