# OWNER'S MANUAL - PRODUCT FICHE

RELATED OWNER'S MANUAL CODE: 16122000A65955

| Trade Mark | Rotenso | | | |
|---|---|---|---|---|
| Indoor Model | I26Xi R14 | I35Xi R14 | I50Xi R14 | I70Xi R14 |
| Outdoor Model | I26Xo R14 | I35Xo R14 | I50Xo R14 | I70Xo R14 |
| Sound Power Level at Standard Rating Conditions(Indoor/Outdoor)[dB(A)] | 55/60 | 55/62 | 57/65 | 64/67 |
| Refrigerant Type | R32 | R32 | R32 | R32 |
| GWP | 675 | 675 | 675 | 675 |
| Charge amount (g) | 620 | 620 | 1100 | 1450 |
| CO2 equivalent (tonnes) | 0.42 | 0.42 | 0.74 | 0.98 |
| SEER | 9.3 | 8.5 | 7.0 | 6.5 |
| Energy efficiency Class in cooling | A+++ | A+++ | A++ | A++ |
| Annual Electricity Consumption in Cooling[KWh/y] [1] | 98 | 146 | 265 | 377 |
| Design Load in cooling Mode (Pdesign)[KW] | 2.6 | 3.5 | 5.3 | 7 |
| SCOP (average heating season) | 4.6 | 4.6 | 4.0 | 4.0 |
| Energy efficiency class in heating (average season) | A++ | A++ | A+ | A+ |
| Annual electricity consumption in heating (average season)[KWh/y][2] | 743 | 791 | 1435 | 1730 |
| Warmer heating season | Y | Y | Y | Y |
| Colder heating season | —— | —— | —— | —— |
| Design load in heating mode (Pdesign)[KW] | 2.4 | 2.6 | 4.1 | 4.9 |
| Declared capacity at reference design condition (heating average season)[KW] | 2.034 | 2.091 | 3.393 | 3.690 |
| Back up heating capacity at reference design condition (heating average season)[KW] | 0.366 | 0.509 | 0.707 | 1.210 |

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 675 . This means that if 1kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 675 times higher than 1kg of CO2 , over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional

Contains fluourinated greenhouse gases.

Importer: THERMOSILESIA, ul. Szyb Walenty 16, 41-700 Ruda Śląska, Poland

Manufacturer: ROTENSO, ul. Szyb Walenty 16, 41-700 Ruda Śląska, Poland

[1] [2] Energy consumption “XYZ” kWh per year, based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.

Note: Please check the model information above according to the model name on the nameplate.

# KARTA PRODUKTU

KOD KARTY PRODUKTU: 16122000A65955

| Znak towarowy | Rotenso | | | |
|---|---|---|---|---|
| Jednostka wewnętrzna | I26Xi R14 | I35Xi R14 | I50Xi R14 | I70Xi R14 |
| Jednostka zewnętrzna | I26Xo R14 | I35Xo R14 | I50Xo R14 | I70Xo R14 |
| Poziom mocy akustycznej (jednostka wewnętrzna/jednostka zewnętrzna [dB(A)] | 55/60 | 55/62 | 57/65 | 64/67 |
| Rodzaj czynnika chłodniczego | R32 | R32 | R32 | R32 |
| GWP | 675 | 675 | 675 | 675 |
| Ilość czynnika chłodnczego (g) | 620 | 620 | 1100 | 1450 |
| Ekwiwalent CO2 (tCO2eq) | 0.42 | 0.42 | 0.74 | 0.98 |
| SEER | 9.3 | 8.5 | 7.0 | 6.5 |
| Klasa efektywności - chłodzenie | A+++ | A+++ | A++ | A++ |
| Roczne zużycie energii elektrycznej - funkcja chłodzenia [KWh/y] [1] | 98 | 146 | 265 | 377 |
| Obciążenie chłodnicze [KW] | 2.6 | 3.5 | 5.3 | 7 |
| SCOP | 4.6 | 4.6 | 4.0 | 4.0 |
| Klasa efektywności - grzanie | A++ | A++ | A+ | A+ |
| Roczne zużycie energii elektrycznej - funkcja grzania [KWh/y] [2] | 743 | 791 | 1435 | 1730 |
| Sezon grzewczy cieplejszy | Y | Y | Y | Y |
| Sezon grzewczy chłodniejszy | ——— | ——— | ——— | ——— |
| Obciążenie grzewcze [KW] | 2.4 | 2.6 | 4.1 | 4.9 |
| Deklarowana wydajność w warunkach ogrzewania (średni sezon) [KW] | 2.034 | 2.091 | 3.393 | 3.690 |
| Zapas mocy w warunkach ogrzewania (średni sezon) [KW] | 0.366 | 0.509 | 0.707 | 1.210 |

Wycieki czynników chłodniczych przyczyniają się do zmiany klimatu. W przypadku przedostania się do atmosfery czynnika chłodniczego o niższym współczynniku ocieplenia globalnego (GWP) ma mniejszy wpływ na globalne ocieplenie niż czynnik o wyższym współczynniku GWP. Urządzenie zawiera płyn chłodniczy o współczynniku GWP wynoszącym [ 675 ]. Powyższe oznacza, iż w przypadku przedostanie się 1 kg takiego płynu chłodniczego do atmosfery, jego wpływ na globalne ocieplenie byłby [ 675 ] razy większy niż wpływ 1 kg CO2 w okresie 100 lat. Nigdy nie należy samodzielnie manipulować przy obiegu czynnika lub demontować urządzeń, należy zawsze zwrócić się o pomoc do specjalisty.

Zawiera fluorowane gazy cieplarniane.

Importer: THERMOSILESIA, ul. Szyb Walenty 16, 41-700 Ruda Śląska, Poland

Manufacturer: ROTENSO, ul. Szyb Walenty 16, 41-700 Ruda Śląska, Poland

[1] [2] Zużycie energii „XYZ” kWh na rok, oparte na standardowych wynikach testu. Rzeczywiste zużycie energii zależy od sposobu użytkowania urządzenia i jego umiejscowienia.

Uwaga: Proszę sprawdzić powyższe informacje o urządzeniu czy zgadzają się z nazwą modelu na tabliczce znamionowej.

# OWNER'S MANUAL - PRODUCT FICHE

RELATED OWNER'S MANUAL CODE: CS001UI-AB(D)

| Trade Mark | | Rotenso | | | |
|---|---|---|---|---|---|
| Model: Indoor | | I26Xi R14 | I35Xi R14 | I50Xi R14 | I70Xi R14 |
| Model: Outdoor | | I26Xo R14 | I35Xo R14 | I50Xo R14 | I70Xo R14 |
| Sound power level at standard rating conditions (Indoor/Outdoor) | [dB(A)] | 55/60 | 55/62 | 57/65 | 64/67 |
| Refrigerant type | | R32 | R32 | R32 | R32 |
| GWP [1] | | 675 | 675 | 675 | 675 |
| Charge amount [1] | [g] | 620 | 620 | 1100 | 1450 |
| CO2 equivalent [1] | [tonnes] | 0.418 | 0.418 | 0.74 | 0.978 |
| SEER | [W/W] | 9.3 | 8.5 | 7.0 | 6.5 |
| Energy efficiency class in cooling | | A+++ | A+++ | A++ | A++ |
| Annual electricity consumption in cooling [2] | [kWh/a] | 98 | 146 | 265 | 377 |
| Design load in cooling mode (Pdesign) | [kW] | 2.6 | 3.5 | 5.3 | 7.0 |
| SCOP (average heating season) | [W/W] | 4.6 | 4.6 | 4.0 | 4.0 |
| Energy efficiency class in heating (average season) | | A++ | A++ | A+ | A+ |
| Annual electricity consumption in heating (average season) [2] | [kWh/a] | 743 | 791 | 1435 | 1730 |
| Design load in heating mode (Pdesign) | [kW] | 2.4 | 2.6 | 4.1 | 4.9 |
| Declared capacity at reference design condition (Average) | [kW] | 2.034 | 2.091 | 3.393 | 3.690 |
| Back up heating capacity at reference design condition (Average) | [kW] | 0.366 | 0.509 | 0.707 | 1.210 |
| SCOP (Warmer) | [W/W] | 6.0 | 6.1 | 5.1 | 5.1 |
| Energy efficiency class in heating (Warmer) | | A+++ | A+++ | A+++ | A+++ |
| Annual electricity consumption in heating (Warmer) [2] | [kWh/a] | 630 | 689 | 1308 | 1545 |
| Design load in heating mode (Pdesign) (Warmer) | [kW] | 2.7 | 3.0 | 4.5 | 5.3 |
| Declared capacity at reference design condition (Warmer) | [kW] | 2.700 | 3.000 | 4.500 | 5.300 |
| Back up heating capacity at reference design condition (Warmer) | [kW] | 0.000 | 0.000 | 0.000 | 0.000 |
| SCOP (Colder) | [W/W] | 3.6 | 3.6 | 3.1 | 2.8 |
| Energy efficiency class in heating (Colder) | | A | A | B | C |
| Annual electricity consumption in heating (Colder) [2] | [kWh/a] | 2158 | 2042 | 4268 | 7950 |
| Design load in heating mode (Pdesign) (Colder) | [kW] | 3.7 | 3.5 | 6.3 | 10.6 |
| Declared capacity at reference design condition (Colder) | [kW] | 1.582 | 1.489 | 2.732 | 3.853 |
| Back up heating capacity at reference design condition (Colder) | [kW] | 2.118 | 2.011 | 3.568 | 6.747 |

[1] Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to [675]. This means that if 1kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be [675] times higher than 1kg of CO2 , over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional

Contains fluourinated greenhouse gases.

Importer: THERMOSILESIA, ul. Szyb Walenty 16, 41-700 Ruda Śląska, Poland

Manufacturer: ROTENSO, ul. Szyb Walenty 16, 41-700 Ruda Śląska, Poland

[2] Energy consumption “XYZ” kWh per year, based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.

Note: Please check the model information above according to the model name on the nameplate.