

Wall-mounted air conditioner

Teta Mirror TM26X ^[R16]



- SCOP 4,6
- Wi-Fi
- 25°C
- iAIR
- Compressor winding heating
- PZH CERTIFICATE
- 5 year WARRANTY

- DEDICATED TO HEATING
- 1:1 SINGLE
- 1:X MULTI

Unit features

SKY inverter Digital DC Inverter SKY®	Automatic cleaning iAIR	Automatic purification iClean ⁽¹⁾	Super Ionizer iAIR	UV lamp	3-in-1 (Ca + Si.Ion + Vit.C) iAIR filter ^(*)	3-in-1 (Photo. + Act.Carb. + Nano) iAIR filter ^(**)	Electrostatic HD iAIR filter
Super Silent eMOTO mode	Automatic 4D louvres	Windless eMOTO air supply	Turbo eMOTO mode	Air supply eMOTO control system	Eco eMOTO mode	Wide-angle eMOTO air supply	SMART wi-fi
SMART panel display ON/OFF	SMART Follow mode ⁽¹⁾	Wireless remote control	SMART heating to 8°C ⁽¹⁾	Louvre setting memory	Auto restart memory	Anti-corrosive gold fins	Drip tray heater
Compressor winding heating ⁽¹⁾	Timer	Cooling at low outdoor temp. down to -15°C	Heating at low outdoor temp. down to -25°C ⁽¹⁾	Double-sided condensate drainage	Self-diagnostics	Sleep mode	Energy optimization ⁽¹⁾

1. Feature not available in Multi Split system

* 3-in-1 iAIR filter: Catechin + Silver Ion + Vitamin C

** 3-in-1 iAIR filter: Photocatalytic + Activated carbon + Cold Nano

Technical specification

Model				Teta Mirror 2,6 kw	
Capacity	Cooling	Nom. (Min. - Max.)	W	2610 (940-3700)	
Rated input		Nom. (Min. - Max.)	W	699 (240-1380)	
Operating current		Nom. (Min. - Max.)	A	3,0 (1,0-6,0)	
Capacity	Heating	Nom. (Min. - Max.)	W	3000 (940-4000)	
Rated input		Nom. (Min. - Max.)	W	740 (240-1552)	
Operating current		Nom. (Min. - Max.)	A	3,2 (1,0-6,7)	
Reversible heat pump type				air-to-air	
Design load in cooling mode			kW	2,6	
SEER			W/W	8,5	
Energy efficiency class, cooling				A+++	
Annual electric energy consumption, cooling			kWh/a	108	
Design load in heating mode (Tbiv -7°C)			kW	2,4	
SCOP			W/W	4,6	
Energy efficiency class, heating				A++	
Annual electric energy consumption, heating			kWh/a	731	
Dehumidification			l/h	1,0	
Maximum energy consumption			W	1552	
Maximum operating current			A	6,7	
Indoor unit				TM26Xi R16	
EAN product code				5905567606496	
Fan speed	T / H / M / L / ML / S		rpm	1250 / 1080 / 920 / 800 / 700 / 650	
Air flow	T / H / M / L / ML / S		m³/h	560 / 480 / 410 / 360 / 310 / 275	
Sound pressure level	T / H / M / L / ML / S		dB(A)	42 / 38 / 33 / 27 / 21 / 18	
Sound power level			dB(A)	52	
Rated input			W	25	
Operating current			A	0,1	
Net dimensions		W × D × H	mm	790 × 192 × 275	
Gross dimensions		W × D × H	mm	860 × 265 × 345	
Net weight / Gross weight			kg	8,5 / 10,5	
Condensate drain			mm	16	
Outdoor unit				TO26Xo R16	
EAN product code				5905567606502	
Fan speed	T / H / M / L / S		rpm	900 / 810 / 730 / 610 / 450	
Maximum air flow			m³/h	2200	
Sound pressure level			dB(A)	51	
Sound power level			dB(A)	61	
Net dimensions		W × D × H	mm	795 × 305 × 551	
Gross dimensions		W × D × H	mm	835 × 328 × 575	
Bracket spacing		W × D	(mm)	434 × 278	
Net weight / Gross weight			kg	23 / 25	
Refrigerant	Type			R32	
	GWP			675	
	≤ 5m	kg		0,45	
		TCO ₂ eq		0,304	
Charged (> 5m)		g/mb		15	
Pipe connections		Liquid/Gas	mm (inches)	Φ6,35 / Φ9,52 (1/4" / 3/8")	
Maximum installation length			m	25	
Maximum height difference			m	10	
Compressor type				Rotary DC	
Type of outdoor unit power supply			V-Hz, Ø	220-240-50, 1φ	
Electrical protection			A	C10	
Power cables: outdoor unit			pcs × mm²	3 × 1,5	
Control and power cables: indoor unit - outdoor unit			pcs × mm²	5 × 1,5	
Control and power cables: hiro unit - indoor unit			pcs × mm²	4 × 1	
Indoor operating range (Cooling / Heating)			°C	16-32 / 0-30	
Outdoor operating range (Cooling / Heating)			°C	-15-53 / -25-30	
Compatible systems					
1:1 SINGLE				●	
1:2 DUAL					
1:X MULTI S-Line					
1:X MULTI N-Line				●	