



































Wall-mounted air conditioner

Teta TA26X ^[R16]



Unit features

 Digital DC Inverter SKY [®]	 Automatic cleaning iAIR	 Automatic purification iClean ⁽¹⁾	 Super Ionizer iAIR	 UV lamp	 3-in-1 (Ca + Si.Ion + Vit.C) iAIR filter ^(*)	 3-in-1 (Photo. + Act.Carb. + Nano) iAIR filter ^(**)	 Electrostatic HD iAIR filter
 Super Silent eMOTO mode	 Automatic 4D louvres	 Windless eMOTO air supply	 Turbo eMOTO mode	 Air supply eMOTO control system	 Eco eMOTO mode	 Wide-angle eMOTO air supply	 SMART wi-fi
 SMART panel display ON/OFF	 SMART Follow mode ⁽¹⁾	 Wireless remote control	 SMART heating to 8°C ⁽¹⁾	 Louvre setting memory	 Auto restart memory	 Anti-corrosive gold fins	 Drip tray heater
 Compressor winding heating ⁽¹⁾	 Timer	 Cooling at low outdoor temp. down to -15°C	 Heating at low outdoor temp. down to -25°C ⁽¹⁾	 Double-sided condensate drainage	 Self-diagnostics	 Sleep mode	 Energy optimization ⁽¹⁾

1. Feature not available in Multi Split system

* 3-in-1 iAIR filter: Catechin + Silver Ion + Vitamin C

** 3-in-1 iAIR filter: Photocatalytic + Activated carbon + Cold Nano

Technical specification

Model				Teta 2,6 kw
Capacity	Cooling	Nom. (Min. - Max.)	W	2610 (940-3700)
Rated input		Nom. (Min. - Max.)	W	699 (240-1380)
Operating current		Nom. (Min. - Max.)	A	3,0 (1,0-6,0)
Capacity	Heating	Nom. (Min. - Max.)	W	3000 (940-4000)
Rated input		Nom. (Min. - Max.)	W	740 (240-1552)
Operating current		Nom. (Min. - Max.)	A	3,2 (1,0-6,7)
Reversible heat pump type				air-to-air
Design load in cooling mode			kW	2,6
SEER			W/W	8,5
Energy efficiency class, cooling				A+++
Annual electric energy consumption, cooling			kWh/a	108
Design load in heating mode (Tbiv -7°C)			kW	2,4
SCOP			W/W	4,6
Energy efficiency class, heating				A++
Annual electric energy consumption, heating			kWh/a	731
Dehumidification			l/h	1,0
Maximum energy consumption			W	1552
Maximum operating current			A	6,7
Indoor unit				TA26Xi R16
EAN product code				5905567606489
Fan speed	T / H / M / L / ML / S		rpm	1250 / 1080 / 920 / 800 / 700 / 650
Air flow	T / H / M / L / ML / S		m³/h	560 / 480 / 410 / 360 / 310 / 275
Sound pressure level	T / H / M / L / ML / S		dB(A)	42 / 38 / 33 / 27 / 21 / 18
Sound power level			dB(A)	52
Rated input			W	25
Operating current			A	0,1
Net dimensions		W × D × H	mm	790 × 192 × 275
Gross dimensions		W × D × H	mm	860 × 265 × 345
Net weight / Gross weight			kg	8,5 / 10,5
Condensate drain			mm	16
Outdoor unit				TO26Xo R16
EAN product code				5905567606502
Fan speed	T / H / M / L / S		rpm	900 / 810 / 730 / 610 / 450
Maximum air flow			m³/h	2200
Sound pressure level			dB(A)	51
Sound power level			dB(A)	61
Net dimensions		W × D × H	mm	795 × 305 × 551
Gross dimensions		W × D × H	mm	835 × 328 × 575
Bracket spacing		W × D	(mm)	434 × 278
Net weight / Gross weight			kg	23 / 25
Refrigerant	Type			R32
	GWP			675
	≤ 5m	kg		0,45
		TCO ₂ eq		0,304
Charged (> 5m)		g/mb		15
Pipe connections		Liquid/Gas	mm (inches)	"Φ6,35 / Φ9,52 (1/4" / 3/8")"
Maximum installation length			m	25
Maximum height difference			m	10
Compressor type				Rotary DC
Type of outdoor unit power supply			V-Hz, Ø	220-240-50, 1f
Electrical protection			A	C10
Power cables: outdoor unit			pcs × mm²	3 × 1,5
Control and power cables: indoor unit - outdoor unit			pcs × mm²	5 × 1,5
Control and power cables: hiro unit - indoor unit			pcs × mm²	4 × 1
Indoor operating range (Cooling / Heating)			°C	16-32 / 0-30
Outdoor operating range (Cooling / Heating)			°C	-15-53 / -25-30
Compatible systems				
1:1 SINGLE				•
1:2 DUAL				
1:X MULTI S-Line				
1:X MULTI N-Line				•