

Wall-mounted air conditioner

Versu Mirror VM26X ^[R15]

S-LINE

HP-LINE



- SCOP 4,6
- Wi-Fi
- 22°C
- iClean
- Heating coil
- PZH CERTIFICATE
- 5 year WARRANTY

DEDICATED TO HEATING

1:1 SINGLE

1:X MULTI

Unit features



Digital DC Inverter SKY[®]



Automatic purification iClean ⁽¹⁾



Super Ionizer iAIR



3-in-1 (Si.Ion + Photocat. + Nano) iAIR filter ⁽²⁾



Antibacterial HEPA iAIR filter



Electrostatic HD iAIR filter



Super Silent eMOTO mode ⁽¹⁾



Automatic 4D louvres



Rotating louvre 180°



Turbo eMOTO mode ⁽¹⁾



Upwards cascade air supply



Downwards cascade air supply



Air supply eMOTO control system



Eco eMOTO mode ⁽¹⁾



Wide-angle eMOTO air supply



Humidity sensor ⁽¹⁾⁽³⁾



Wired controller SMART port ⁽²⁾



SMART Wi-Fi



SMART panel display ON/OFF



SMART Follow mode



Wireless remote control



Wired controller ⁽²⁾



SMART heating to 8°C ⁽¹⁾



Louvre setting memory



1W standby mode ⁽¹⁾



Auto restart memory



Anti-corrosive gold fins



Drip tray heater



Compressor crankcase heater



Silence mode



Timer



Cooling at low outdoor temp down to -15°C



Heating at low outdoor temp. down to -22°C ⁽¹⁾



Double-sided condensate drainage



Self-diagnostics



Sleep mode



BMS Modbus ⁽²⁾



BMS Bacnet ⁽²⁾

1. Feature not available in Multi Split system. 2. Feature is only optional. 3. Feature can be accessed via mobile app.

* Silver Ion + Photocatalytic + Cold Nano

Technical specification

Model				Versu Mirror 2,6 kW
Capacity	Cooling	Nom. (Min. - Max.)	W	2638 (1231-3297)
Rated input		Nom. (Min. - Max.)	W	600 (100-1260)
Operating current		Nom. (Min. - Max.)	A	2,6 (0,4-5,5)
Capacity	Heating	Nom. (Min. - Max.)	W	2931 (847-3722)
Rated input		Nom. (Min. - Max.)	W	623 (110-1320)
Operating current		Nom. (Min. - Max.)	A	2,7 (0,5-5,7)
Reversible heat pump type				air-to-air
Design load in cooling mode			kW	2,6
SEER			W/W	8,8
Energy efficiency class, cooling				A+++
Annual electric energy consumption, cooling			kWh/a	103
Design load in heating mode (Tbiv -7°C)			kW	2,5
SCOP			W/W	4,6
Energy efficiency class, heating				A++
Annual electric energy consumption, heating			kWh/a	776
Dehumidification			l/h	1,0
Maximum energy consumption			W	2200
Maximum operating current			A	9,6
Indoor unit				VM26Xi R15
EAN product code				5905567600890
Fan speed	T / H / M / L / ML / S		rpm	1122 / 910 / 823 / 710 / 652 / 600
Air flow	T / H / M / L / ML / S		m³/h	700 / 555 / 445 / 380 / 270 / 230
Sound pressure level	T / H / M / L / ML / S		dB(A)	40 / 32 / 27 / 24 / 21 / 19
Sound power level			dB(A)	53
Rated input			W	13
Operating current			A	0,1
Net dimensions		W × D × H	mm	920 × 211 × 321
Gross dimensions		W × D × H	mm	1005 × 295 × 385
Net weight / Gross weight			kg	11,3 / 14,2
Condensate drain			mm	16
Outdoor unit				VM26Xo R15
EAN product code				5905567600906
Fan speed	H / M / L		rpm	800 / 620 / 450
Maximum air flow			m³/h	2200
Sound pressure level			dB(A)	53
Sound power level			dB(A)	58
Net dimensions		W × D × H	mm	765 × 303 × 555
Gross dimensions		W × D × H	mm	887 × 337 × 610
Bracket spacing		W × D	(mm)	452 × 286
Net weight / Gross weight			kg	26,4 / 28,8
Refrigerant	Type			R32
	GWP			675
	≤ 5m	kg		0,7
		TCO ₂ eq		0,47
Charged > 5m		g/mb		12
Pipe connections		Liquid/Gas	mm (inches)	Φ6,35 / Φ9,52 (1/4" / 3/8")
Maximum installation length			m	25
Maximum height difference			m	10
Compressor type				Rotary DC
Type of outdoor unit power supply			V-Hz, Ø	220-240-50, 1f
Electrical protection			A	C10
Power cables: outdoor unit			pcs × mm²	3 × 1,5
Control and power cables: indoor unit - outdoor unit			pcs × mm²	5 × 1,5
Control and power cables: hiro unit - indoor unit			pcs × mm²	4 × 1,5
Indoor operating range (cooling / heating)			°C	16~32 / 0~30
Outdoor operating range (cooling / heating)			°C	-15~50 / -22~30
Compatible systems				
1:1 SINGLE				•
1:2 DUAL				
1:X MULTI S-Line				•
1:X MULTI N-Line				
1:X MULTI HP-Line				•