

Wall-mounted air conditioner

Elis Silver ES26X^[R17]



Features device

							
Digital DC Inverter SKY®	Automatic cleaning iAIR	Automatic purification iClean ⁽¹⁾	3-in-1 (Ca + Si, Ion + Vit. C) iAIR filter ^(*)	3-in-1 (Photo. + Act. Carb. + Nano) iAIR filter ^(**)	Electrostatic HD iAIR filter	Super Silent eMOTO mode	Automatic 4D louvers
							
Turbo eMOTO mode	Air supply eMOTO control system	ECO eMOTO mode	Wide-angle eMOTO air supply	SMART Wi-Fi	SMART panel display ON/OFF	SMART Follow mode ⁽¹⁾	Wireless remote control
							
SMART heating to 8°C ⁽¹⁾	Auto restart memory	Anti-corrosive gold fins	Timer	Cooling at low outdoor temp. down to -15°C	Heating at low outdoor temp. down to -20°C	Double-sided condensate drainage	Self-diagnostics
							
Sleep mode							

1. Feature not available in Multi Split system

* 3-in-1 iAIR filter: Catechin + Silver Ion + Vitamin C

** 3-in-1 iAIR filter: Photocatalytic + Activated carbon + Cold Nano

Technical specification

Model				Elis Silver 2,6 kW
Capacity	Cooling	Nom. (Min. - Max.)	W	2600 (940-3300)
Rated input		Nom. (Min. - Max.)	W	851 (240-1380)
Operating current		Nom. (Min. - Max.)	A	3,7 (1-6,0)
Capacity	Heating	Nom. (Min. - Max.)	W	2680 (940-3200)
Rated input		Nom. (Min. - Max.)	W	786 (240-1552)
Operating current		Nom. (Min. - Max.)	A	3,4 (1-6,7)
Reversible heat pump type				air-to-air
Design load in cooling mode			kW	2,6
SEER			W/W	6,1
Energy efficiency class, cooling				A++
Annual electric energy consumption, cooling			kWh/a	150
Design load in heating mode (Tbiv -7°C)			kW	2,0
SCOP			W/W	4,0
Energy efficiency class, heating				A+
Annual electric energy consumption, heating			kWh/a	700
Dehumidification			l/h	1,0
Maximum energy consumption			W	1552
Maximum operating current			A	6,7
Indoor unit				ES26Xi R17
EAN product code				5905567614279
Fan speed	T / H / M / L / S	rpm	1400 / 1300 / 1100 / 1050 / 900	
Air flow	T / H / M / L / S	m³/h	420 / 390 / 330 / 320 / 270	
Sound pressure level	T / H / M / L / S	dB(A)	42 / 37 / 33 / 25 / 22	
Sound power level		dB(A)	52	
Rated input		W	30	
Operating current		A	0,1	
Net dimensions	W × D × H	mm	698 × 205 × 255	
Gross dimensions	W × D × H	mm	765 × 260 × 335	
Net weight / Gross weight		kg	6,5 / 8,5	
Condensate drain		mm	16	
Outdoor unit				EO26Xo R17
EAN product code				5905567614361
Fan speed	H / M / L	rpm	930 / 930 / 830 / 730 / 630	
Maximum air flow		m³/h	1700	
Sound pressure level		dB(A)	52	
Sound power level		dB(A)	62	
Net dimensions	W × D × H	mm	740 × 253 × 459	
Gross dimensions	W × D × H	mm	765 × 310 × 481	
Bracket spacing	W × D	(mm)	362 × 256	
Net weight / Gross weight		kg	19 / 21	
Refrigerant	Type		R32	
	GWP		675	
	≤ 5m	kg	0,49	
		TCO ₂ eq	0,33	
	Charged (> 5m)	g/mb	12	
Pipe connections	Liquid/Gas	mm (inches)	Φ6,35 / Φ9,52 (1/4" / 3/8")	
Maximum installation length		m	25	
Maximum height difference		m	10	
Compressor type				Rotary DC
Type of outdoor unit power supply		V-Hz, Ø	220-240-50, 1f	
Electrical protection		A	B10	
Power cables: outdoor unit		pcs × mm²	3 × 1,5	
Control and power cables: indoor unit - outdoor unit		pcs × mm²	4 × 1	
Control and power cables: hiro unit - indoor unit		pcs × mm²	4 × 1	
Indoor operating range (Cooling / Heating)		°C	16~32 / 0~30	
Outdoor operating range (Cooling / Heating)		°C	-15~53 / -20~30	
Compatible systems				
1:1 SINGLE				●
1:2 DUAL				
1:X MULTI S-Line				
1:X MULTI N-Line				●
1:X MULTI HP-Line				

T - Turbo; H - High; M - Medium; L - Low; S - Silent;