

# Wall-mounted air conditioner

Versu Mirror VM26X <sup>[R14]</sup>



## Unit features

- |                                     |  |   |                                      |                                    |                                  |  |                          |
|-------------------------------------|--|---|--------------------------------------|------------------------------------|----------------------------------|--|--------------------------|
| <br>Digital DC Inverter SKY®        | <br>Automatic cleaning iAIR <sup>(1)</sup>     | <br>Super Ionizer iAIR  | <br>Cold Nano iAIR filter            | <br>Antibacterial HEPA iAIR filter | <br>Electrostatic HD iAIR filter | <br>Super Silent eMOTO mode <sup>(1)</sup>     | <br>Automatic 4D louvres |
| <br>Turbo eMOTO mode <sup>(1)</sup> | <br>Air supply eMOTO control system            | <br>Eco eMOTO mode <sup>(1)</sup>                             | <br>Wide-angle eMOTO air supply      | <br>SMART wi-fi                    | <br>SMART twilight sensor        | <br>Wired controller SMART port <sup>(2)</sup> | <br>SMART Follow mode    |
| <br>Wireless remote control         | <br>Wired controller <sup>(2)</sup>            | <br>SMART heating to 8°C <sup>(1)</sup>                       | <br>Louvre setting memory            | <br>1W standby mode <sup>(1)</sup> | <br>Auto restart memory          | <br>Anti-corrosive gold fins                   | <br>Drip tray heater     |
| <br>Compressor crankcase heater     | <br>Cooling at low outdoor temp. down to -15°C | <br>Heating at low outdoor temp. down to -22°C <sup>(1)</sup> | <br>Double-sided condensate drainage | <br>Self-diagnostics               | <br>Sleep mode                   |  |                          |

# Technical specification

Model				Versu Mirror 2,6 kW
Capacity	Cooling	Nom. (Min. - Max.)	W	2638 (1231-3224)
Rated input		Nom. (Min. - Max.)	W	613 (90-1140)
Operating current		Nom. (Min. - Max.)	A	2,7 (0,4-4,9)
Capacity	Heating	Nom. (Min. - Max.)	W	2931 (820-3703)
Rated input		Nom. (Min. - Max.)	W	637 (110-1080)
Operating current		Nom. (Min. - Max.)	A	2,8 (0,5-4,7)
Reversible heat pump type				air-to-air
Design load in cooling mode			kW	2,6
SEER			W/W	8,6
Energy efficiency class, cooling				A+++
Annual electric energy consumption, cooling			kWh/a	107
Design load in heating mode (Tbiv -7°C)			kW	2,5
SCOP			W/W	4,6
Energy efficiency class, heating				A++
Annual electric energy consumption, heating			kWh/a	775
Dehumidification			l/h	1
Maximum energy consumption			W	2200
Maximum operating current			A	9,6
Indoor unit				VM26Xi R14
Fan speed	H / M / L / S		rpm	1150 / 950 / 850 / 750
Air flow	H / M / L / S		m³/h	558 / 478 / 384 / 240
Sound pressure level	H / M / L / S		dB(A)	37 / 26 / 22 / 20
Sound power level			dB(A)	51
Rated input			W	26
Operating current			A	0,1
Net dimensions	W × D × H		mm	897 × 182 × 312
Gross dimensions	W × D × H		mm	985 × 260 × 385
Net weight / Gross weight			kg	10,5 / 14,2
Condensate drain			mm	16
Outdoor unit				VO26Xo R14
Fan speed	H / M / L		rpm	800 / 620 / 450
Maximum air flow			m³/h	2150
Sound pressure level			dB(A)	54
Sound power level			dB(A)	60
Net dimensions	W × D × H		mm	765 × 303 × 555
Gross dimensions	W × D × H		mm	887 × 337 × 610
Bracket spacing	W × D		(mm)	452 × 286
Net weight / Gross weight			kg	26,7 / 29,1
Refrigerant	Type			R32
	GWP			675
	≤ 5m	kg		0,62
		TCO <sub>2</sub> eq		0,42
Charged > 5m	g/mb		12	
Pipe connections	Liquid/Gas		mm (inches)	Φ6,35 / Φ9,52 (1/4" / 3/8")
Maximum installation length			m	25
Maximum height difference			m	10
Compressor type				Rotary DC
Type of outdoor unit power supply			V-Hz, Ø	220-240-50, 1φ
Electrical protection			A	C10
Power cables: outdoor unit			pcs × mm²	3 × 1,5
Control and power cables: indoor unit - outdoor unit			pcs × mm²	5 × 1,5
Control and power cables: hiro unit - indoor unit			pcs × mm²	4 × 1,5
Indoor operating range (Cooling / Heating)			°C	17~32 / 0~30
Outdoor operating range (Cooling / Heating)			°C	-15~50 / -22~30
Compatible systems				
1:1 SINGLE				•
1:2 DUAL				
1:X MULTI				•

H - High; M - Medium; L - Low; S - Silent