
Room Air Conditioner

Ukura U21X [R17]

S-LINE

HP-LINE





SCOP 4.1

-20°C

4D

1: 1 SINGLE

1: X MULTI

Key features of the device

- SKY® Digital DC Inverter
- iClean Automatic purification (1)
- iAIR Super Ionizer
- iAIR Cold Nano filter
- iAIR Filter with antibacterial properties
- iAIR HD pre-filter
- eMOTO Super silent mode (1)
- Automatic 4D louvres
- eMOTO Turbo mode (1)
- eMOTO Airflow control system
- Louvre setting memory
- Eco SMART function (1)
- eMOTO Wide-angle airflow
- SMART Wi-Fi function
- SMART wired controller port (2)
- Smart panel display ON/OFF
- SMART Follow mode
- Wireless remote controller
- Wired controller (2)
- SMART heating 8°C function (1)
- 1W standby mode (1)
- Auto restart memory
- Anti-corrosive gold-plated fins
- Silence mode (1)
- Timer
- Cooling at low ext. temp. -15°C
- Heating at low ext. temp. -20°C
- Double-sided condensate drainage
- Self-diagnosis function
- Sleep mode
- Remote On/Off output (3)
- BMS Modbus (3)
- BMS Bacnet (3)

1. Function not available in the Multi Split system. 2. This function is available as an option or as standard with the ZATO X wired controller. 3. Function available as an option.

PRODUCT SHEET

Rotenso Sp. z o.o. reserves the right to make changes to products without prior notice.

Technical Specification

Model				**Ukura 2.1 kW**
Capacity	Cooling	Nom. (Min. - Max.)	W	2,100 (880-2,460)
Rated input		Nom. (Min. - Max.)	W	620 (100-820)
Operating current		Nom. (Min. - Max.)	A	2.7 (0.4-3.6)
Capacity	Heating	Nom. (Min. - Max.)	W	2,400 (730-2,700)
Rated input		Nom. (Min. - Max.)	W	650 (120-780)
Operating current		Nom. (Min. - Max.)	A	2.8 (0.5-3.4)
Reversible heat pump type				air-to-air
Design load in cooling mode			kW	2.1
SEER			W/W	7.1
Energy efficiency class for cooling				A++
Annual electric energy consumption - cooling			kWh/a	104
Design load in heating mode (Tbiv -7°C)			kW	1.8
SCOP			W/W	4.1
Energy efficiency class - heating				A+
Annual electric energy consumption - heating			kWh/a	615
Dehumidification			l/h	0.9
Maximum energy consumption			W	2,030
Maximum operating current			A	8.8

Indoor unit			**U21Xi R17**
EAN product code			5905567608827
Fan speed	H / M / L / S	rpm	1,050 / 930 / 900 / 870
Air flow	H / M / L / S	m³/h	490 / 360 / 300 / 140
Sound pressure level	H / M / L / S	dB(A)	37.5 / 32 / 23 / 18
Sound power level		dB(A)	54
Rated input		W	23
Operating current		A	0.1
Net dimensions	W × D × H	mm	723 × 199 × 286
Gross dimensions	W × D × H	mm	780 × 270 × 365
Net Weight / Gross Weight		kg	6.9 / 9.1
Condensate drain		mm	16

Outdoor unit			**U21Xo R17**
EAN product code			5905567608834
Fan speed	H / M / L	rpm	850 / 740 / 650
Maximum air flow		m³/h	1,300
Sound pressure level		dB(A)	51.5
Sound power level		dB(A)	59
Net dimensions	W × D × H	mm	724 × 252 × 469
Gross dimensions	W × D × H	mm	765 × 270 × 525
Bracket spacing	W × D	(mm)	430 × 231
Net Weight / Gross Weight		kg	17.8 / 19.5
Refrigerant	Type		R32
	Global Warming Potential (GWP)		675
	Charge (up to 5m)	kg	0.40
		TCO_2eq	0.270
	Charge (more than 5m)	g/m	12
Pipe connections	Liquid / Gas	mm (inches)	Φ6.35 / Φ9.52 (1/4" / 3/8")
Maximum installation length		m	25
Maximum height difference		m	10
Compressor type			Rotary DC
Type of outdoor unit power supply		V-Hz, Ø	220-240~50, 1ph
Protection		A	B10
Power cables: outdoor unit	L < 20 m	qty. × mm²	More information can be found in the Hiro product sheet
Control and power cables: outdoor unit - indoor unit		qty. × mm²	5 × 1.5
Control and power cables: Hiro unit - indoor unit		qty. × mm²	4 × 1.5
Indoor operating range (Cooling / Heating)		°C	16~32 / 0~30
Outdoor operating range (Cooling / Heating)		°C	-15~50 / -20~24

Compatible systems	
1:1 SINGLE	•
1:2 DUAL	
1:X MULTI S-Line	•
1:X MULTI N-Line	
1:X MULTI HP-Line	•

H - High; M - Medium; L - Low; S - Silent;

Rotenso Sp. z o.o. reserves the right to make changes to products without prior notice.